



BEND RELIEF-2B P/N DESCRIPTION :

RB003 XX X 0  
① ②

① Corresponding Cable

- 22=2.2mm (Cable $\phi$ 1.4~2.2mm)
- 32=3.2mm (Cable $\phi$ 2.2~3.2mm)
- 42=4.2mm (Cable $\phi$ 3.2~4.2mm)
- 52=5.2mm (Cable $\phi$ 4.2~5.2mm)
- 62=6.2mm (Cable $\phi$ 5.2~6.2mm)
- 72=7.2mm (Cable $\phi$ 6.2~7.2mm)
- 82=8.2mm (Cable $\phi$ 7.2~8.2mm)
- 92=9.2mm (Cable $\phi$ 8.2~9.2mm)
- 99=9.9mm (Cable $\phi$ 9.2~9.9mm)

② Colour

- A=Blue
- G=Grey
- N=Black
- R=Red

NOTES :

- 1.MATERIAL:TPU(THERMOPLASTIC POLYURETHANE)
- 2.TEMPERATURE RANGE IN DRY ATMOSPHERE:-40°C+80°C
- 3.ALL DIMENSIONS ARE IN MILLIMETERS
- 4.RoHS DIRECTIVE COMPLANCE

THIRD ANGLE PROJECTION 		TOLERANCES UNLESS OTHERWISE SPECIFIED		 <b>Dongguan Circon Technology Co.,Ltd.</b>						
UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH		0 PLC $\pm$ 1.00 1 PLC $\pm$ 0.50 2 PLC $\pm$ 0.25 3 PLC $\pm$ 4 PLC $\pm$				TITLE: BEND RELIEF-2B				
APPROVED BY	JACK	DATE	2017-9-18	C	DRAWING NO.	R-B-003	REV.	AO		
CHECKED BY	CHARLES	DATE	2017-9-18		PART NO.	RB003XXX0				
REV.	REVISION DESCRIPTION	ECR/ECN NO.	DATE	DRAWN BY	ANDY	DATE	2017-9-18	SIZE: A3	SCALE: 1:1	SHEET: 1 OF 1